- 1. (15%) [1-A] Describe the ADT (Abstract Data Type) of queue data structure. (3%)
  - [1-B] Describe the ADT of binary tree data structure. (4%)
  - [1-C] Show an implementation of your ADT given in [1-A] using your ADT given in [1-B]. (8%)
- 2. (15%) Given a data set of N records as described below:

Field Name	Description	Attribute	Format
NAME	Name	String of Chinese characters	4 Chinese characters
ID_NO	ID Number	10-byte string	A99999999
DOB	Date of Birth	8-byte data field	MMDDYYYY
TEL_NO	Telephone No.	10-byte string	999999999
ADDR	Address	String of Chinese characters	32 Chinese characters

(Note on format: A=Alphabet, 9=Digit, MM=Month, DD=Day, YYYY=Year)

To sort the N records in non-decreasing order with the conditions given below, answer each question and briefly explain your reason:

- [2-A] If N=100, the key is YYYY and the records with the same key value must keep the same ordering before and after sorting. Which sorting algorithm will you use?
- [2-B] Which sorting algorithm will you use if N=1000 and the key is TEL NO?
- [2-C] Which sorting algorithm will you use if N=100000 and the key is ID NO?
- 3. (5%) Let A be the root node of a binary tree T. Suppose T has 13 nodes and the left subtree of A is a complete binary tree of 5 nodes. How many different structures can T assume?
- 4. (15%) Explain the following terms: (3 points each)

[4-A] Open addressing

[4-B] Dynamic hashing

[4-C] Spanning tree of Graph G

[4-D] Breadth-First Search of Graph G

百

[4-E] Balance factor

- 5. (5%) Transfer an infix expression to a prefix expression.  $7*2/(5-2)-3*(2^8+4+5)/6$
- 6. (5%) Describe advantage(s) and disadvantage(s) of circular queues.
- 7. (10%) There are ten identical objects and one of them is slightly heavier than the others.

  Use a scale a minimum number of times to identify the heavier object. Represent the solution to this problem by a tree.
- 8. (15%) Devise an algorithm to determine whether a given binary tree is a heap.
- 9. (15%) Suppose A is a one-dimensional array of size N and we want to keep K stacks in this array. The size of the ith stack is  $M_i$  and the pointer to the ith stack is  $P_i$ . Organize a storage scheme and the associated <u>PUSH</u> and <u>POP</u> operations.