

國立成功大學

113學年度碩士班招生考試試題

編 號：64

系 所：機械工程學系

科 目：熱力學

日 期：0201

節 次：第 2 節

備 註：可使用計算機

※ 考生請注意：本試題可使用計算機。請於答案卷(卡)作答，於本試題紙上作答者，不予計分。

1. What mechanisms can cause the entropy of a process to increase in a closed system?
(8%)

2. What are the correct statements for the following steady-flow engineering devices?
(multiple choice) (12%)

(a) Turbine:

- [1] working fluid specific volume increases
- [2] working fluid pressure increases
- [3] consumes work
- [4] produces work

(b) Compressor:

- [1] used for gas
- [2] consumes work
- [3] working fluid enthalpy decreases
- [4] working fluid pressure increases

(c) Expansion valve:

- [1] working fluid pressure decreases
- [2] working fluid enthalpy remains constant
- [3] working fluid specific volume increases
- [4] produces work

(d) Nozzle:

- [1] no work device
- [2] working fluid pressure decreases
- [3] working fluid kinetic energy increases
- [4] working fluid enthalpy increases

※ 考生請注意：本試題可使用計算機。請於答案卷(卡)作答，於本試題紙上作答者，不予計分。


Property table for problems 3 and 4

Saturated Water

T (°C)	P (kPa)	v (m ³ /kg)		u (kJ/kg)		h (kJ/kg)		s (kJ/kg-K)	
		v_f	v_g	u_f	u_g	h_f	h_g	s_f	s_g
20	2.339	0.001002	57.7897	83.94	2402.91	83.94	2538.06	0.2966	8.6671

3. A liquid water pump on the ground, taking water in at 20°C, 1 atm(101.3 kPa), at a flow rate of 2 kg/s, brings the pressure up so that the water can be delivered to a receiver tank maintaining a gauge pressure of 500 kPa at the top floor 10 m above ground level. Assume the process is adiabatic and the water stays at 20°C. Also neglect any difference in kinetic energy. Find the required pump work. (10%)

4. A piston/cylinder contains 1 kg water at 20°C with a constant load on the piston such that the pressure is 250 kPa. A nozzle in a line to the cylinder is opened to enable a flow to the outside atmosphere at 100 kPa. The process continues to half the mass has flowed out and there is no heat transfer. Assume water temperature is constant. Find the exit velocity, total work done, and total entropy production in the process. (20%)



Property table for problems 3 and 4

Saturated Water

T (°C)	P (kPa)	v (m ³ /kg)		u (kJ/kg)		h (kJ/kg)		s (kJ/kg-K)	
		v_f	v_g	u_f	u_g	h_f	h_g	s_f	s_g
20	2.339	0.001002	57.7897	83.94	2402.91	83.94	2538.06	0.2966	8.6671

※ 考生請注意：本試題可使用計算機。請於答案卷(卡)作答，於本試題紙上作答者，不予計分。

5. (20%) A gas is described by $v = \frac{RT}{p} - \frac{A}{T} + B$, where A and B are constants. For the gas

(1) (10%) obtain an expression for the temperature at the Joule-Thomson inversion states.

(2) (5%) obtain an expression for $c_p - c_v$.

(3) (5%) For an ideal gas, what is the value of the Joule-Thomson coefficient?

(Hint: $\mu_J = \left(\frac{\partial T}{\partial p}\right)_h$, $\left(\frac{\partial T}{\partial p}\right)_h \left(\frac{\partial p}{\partial h}\right)_T \left(\frac{\partial h}{\partial T}\right)_p = -1$, and $dh = Tds + vdp$)

6. (30%) Air enters the compressor of a cold air-standard Brayton cycle with regeneration and reheat at 100 kPa, 300 K, with a mass flow rate of 5 kg/s. The compressor pressure ratio is 10, and the inlet temperature for each turbine stage is 1500 K. The turbine stages and compressor each have isentropic efficiencies of 80% and the regenerator effectiveness is 80%. For $k = 1.4$ and $c_p = 1.005$ kJ/kg·K,

(1) (5%) sketch the cycle on a T-s chart, and calculate.

(2) (15%) the thermal efficiency of the cycle.

(3) (5%) the back work ratio.

(4) (5%) the net power developed in kW.

T(K), h and u (kJ/kg), s° (kJ/kg·K)											
T	h	u	s°	when Δs = 0 ¹		T	h	u	s°	when Δs = 0	
				p _r	v _r					p _r	v _r
200	199.97	142.56	1.29559	0.3363	1707.	450	451.80	322.62	2.11161	5.775	223.6
210	209.97	149.69	1.34444	0.3987	1512.	460	462.02	329.97	2.13407	6.245	211.4
220	219.97	156.82	1.39105	0.4690	1346.	470	472.24	337.32	2.15604	6.742	200.1
230	230.02	164.00	1.43557	0.5477	1205.	480	482.49	344.70	2.17760	7.268	189.5
240	240.02	171.13	1.47824	0.6355	1084.	490	492.74	352.08	2.19876	7.824	179.7
250	250.05	178.28	1.51917	0.7329	979.	500	503.02	359.49	2.21952	8.411	170.6
260	260.09	185.45	1.55848	0.8405	887.8	510	513.32	366.92	2.23993	9.031	162.1
270	270.11	192.60	1.59634	0.9590	808.0	520	523.63	374.36	2.25997	9.684	154.1
280	280.13	199.75	1.63279	1.0889	738.0	530	533.98	381.84	2.27967	10.37	146.7
285	285.14	203.33	1.65055	1.1584	706.1	540	544.35	389.34	2.29906	11.10	139.7
290	290.16	206.91	1.66802	1.2311	676.1	550	554.74	396.86	2.31809	11.86	133.1
295	295.17	210.49	1.68515	1.3068	647.9	560	565.17	404.42	2.33685	12.66	127.0
300	300.19	214.07	1.70203	1.3860	621.2	570	575.59	411.97	2.35531	13.50	121.2
305	305.22	217.67	1.71865	1.4686	596.0	580	586.04	419.55	2.37348	14.38	115.7
310	310.24	221.25	1.73498	1.5546	572.3	590	596.52	427.15	2.39140	15.31	110.6
315	315.27	224.85	1.75106	1.6442	549.8	600	607.02	434.78	2.40902	16.28	105.8
320	320.29	228.42	1.76690	1.7375	528.6	610	617.53	442.42	2.42644	17.30	101.2
325	325.31	232.02	1.78249	1.8345	508.4	620	628.07	450.09	2.44356	18.36	96.92
330	330.34	235.61	1.79783	1.9352	489.4	630	638.63	457.78	2.46048	19.84	92.84
340	340.42	242.82	1.82790	2.149	454.1	640	649.22	465.50	2.47716	20.64	88.99
350	350.49	250.02	1.85708	2.379	422.2	650	659.84	473.25	2.49364	21.86	85.34
360	360.58	257.24	1.88543	2.626	393.4	660	670.47	481.01	2.50985	23.13	81.89
370	370.67	264.46	1.91313	2.892	367.2	670	681.14	488.81	2.52589	24.46	78.61
380	380.77	271.69	1.94001	3.176	343.4	680	691.82	496.62	2.54175	25.85	75.50
390	390.88	278.93	1.96633	3.481	321.5	690	702.52	504.45	2.55731	27.29	72.56
400	400.98	286.16	1.99194	3.806	301.6	700	713.27	512.33	2.57277	28.80	69.76
410	411.12	293.43	2.01699	4.153	283.3	710	724.04	520.23	2.58810	30.38	67.07
420	421.26	300.69	2.04142	4.522	266.6	720	734.82	528.14	2.60319	32.02	64.53
430	431.43	307.99	2.06533	4.915	251.1	730	745.62	536.07	2.61803	33.72	62.13
440	441.61	315.30	2.08870	5.332	236.8	740	756.44	544.02	2.63280	35.50	59.82

$T(K), h$ and u (kJ/kg), s° (kJ/kg · K)													
				when $\Delta s = 0^\circ$								when $\Delta s = 0$	
T	h	u	s°	p_r	v_r	T	h	u	s°	p_r	v_r		
750	767.29	551.99	2.64737	37.35	57.63	1300	1395.97	1022.82	3.27345	330.9	11.275		
760	778.18	560.01	2.66176	39.27	55.54	1320	1419.76	1040.88	3.29160	352.5	10.747		
770	789.11	568.07	2.67595	41.31	53.39	1340	1443.60	1058.94	3.30959	375.3	10.247		
780	800.03	576.12	2.69013	43.35	51.64	1360	1467.49	1077.10	3.32724	399.1	9.780		
790	810.99	584.21	2.70400	45.55	49.86	1380	1491.44	1095.26	3.34474	424.2	9.337		
800	821.95	592.30	2.71787	47.75	48.08	1400	1515.42	1113.52	3.36200	450.5	8.919		
820	843.98	608.59	2.74504	52.59	44.84	1420	1539.44	1131.77	3.37901	478.0	8.526		
840	866.08	624.95	2.77170	57.60	41.85	1440	1563.51	1150.13	3.39586	506.9	8.153		
860	888.27	641.40	2.79783	63.09	39.12	1460	1587.63	1168.49	3.41247	537.1	7.801		
880	910.56	657.95	2.82344	68.98	36.61	1480	1611.79	1186.95	3.42892	568.8	7.468		
900	932.93	674.58	2.84856	75.29	34.31	1500	1635.97	1205.41	3.44516	601.9	7.152		
920	955.38	691.28	2.87324	82.05	32.18	1520	1660.23	1223.87	3.46120	636.5	6.854		
940	977.92	708.08	2.89748	89.28	30.22	1540	1684.51	1242.43	3.47712	672.8	6.569		
960	1000.55	725.02	2.92128	97.00	28.40	1560	1708.82	1260.99	3.49276	710.5	6.301		
980	1023.25	741.98	2.94468	105.2	26.73	1580	1733.17	1279.65	3.50829	750.0	6.046		
1000	1046.04	758.94	2.96770	114.0	25.17	1600	1757.57	1298.30	3.52364	791.2	5.804		
1020	1068.89	776.10	2.99034	123.4	23.72	1620	1782.00	1316.96	3.53879	834.1	5.574		
1040	1091.85	793.36	3.01260	133.3	22.39	1640	1806.46	1335.72	3.55381	878.9	5.355		
1060	1114.86	810.62	3.03449	143.9	21.14	1660	1830.96	1354.48	3.56867	925.6	5.147		
1080	1137.89	827.88	3.05608	155.2	19.98	1680	1855.50	1373.24	3.58335	974.2	4.949		
1100	1161.07	845.33	3.07732	167.1	18.896	1700	1880.1	1392.7	3.5979	1025	4.761		
1120	1184.28	862.79	3.09825	179.7	17.886	1750	1941.6	1439.8	3.6336	1161	4.328		
1140	1207.57	880.35	3.11883	193.1	16.946	1800	2003.3	1487.2	3.6684	1310	3.944		
1160	1230.92	897.91	3.13916	207.2	16.064	1850	2065.3	1534.9	3.7023	1475	3.601		
1180	1254.34	915.57	3.15916	222.2	15.241	1900	2127.4	1582.6	3.7354	1655	3.295		
1200	1277.79	933.33	3.17888	238.0	14.470	1950	2189.7	1630.6	3.7677	1852	3.022		
1220	1301.31	951.09	3.19834	254.7	13.747	2000	2252.1	1678.7	3.7994	2068	2.776		
1240	1324.93	968.95	3.21751	272.3	13.069	2050	2314.6	1726.8	3.8303	2303	2.555		
1260	1348.55	986.90	3.23638	290.8	12.435	2100	2377.4	1775.3	3.8605	2559	2.356		
1280	1372.24	1004.76	3.25510	310.4	11.835	2150	2440.3	1823.8	3.8901	2837	2.175		
						2200	2503.2	1872.4	3.9191	3138	2.012		
						2250	2566.4	1921.3	3.9474	3464	1.864		

Source: Table A-22 is based on J. H. Keenan and J. Kaye, *Gas Tables*, Wiley, New York, 1945.